



# PORTABLE LOADING DOCK

## SPECS

### STRUCTURAL

---

- Patented Impact-Resistance – absorbs trailer impact forces & remains in position
- High-strength steel frame + solid front safety legs
  - Bolt-down base plates
  - Replaceable open bar traction grating
  - Premium laminated dock bumpers

### OVERALL LENGTH

---

- 38ft. (8' Level Off Loading Deck + 30' Ramp) - Standard/Quick Ship
- Custom Level Off lengths & Longer Ramps available - Built to Order

### CLEAR WIDTH (UNOBSTRUCTED, USABLE SPACE)

---

- 96" - Standard
- 114" - Option
- Custom Clear Width available - Built to Order

### CAPACITY (BASED ON FORKLIFT WEIGHT & MAXIMUM LOAD FOR 8 TRUCKS/DAY)

---

- 16,000 lbs.
- 22,000 lbs.
- 32,000 lbs.

### DOCK LEVELER

---

- Hydraulic Leveler\* (8' L x 83" W) - Standard
  - Cheesegrater® style with open bar grating
  - Exclusive Solar Powered, Push-button Leveler
    - 115V/1Phase/10 Amp power – Option
- Solid Deck Leveler – custom sizes & power available based on application - Built to Order

### SAFETY

---

- Railing:
  - Pedestrian guardrails above 30" of elevation per IBC Code 1013.2
  - Handrails required at 48" of elevation per OSHA Code 1910.23 (c)(1 & 2)
  - Ships Ladder
- Ramp:
  - Recessed sidecurbs for 180-degree forklift turning
  - 13" extra tall, unobstructed side curbs
- Vehicle Departure:
  - Wheel chocks to protect against trailer departure per OSHA 1910.178(k)
  - Trailer restraint per OSHA 1910.178(k) - Option
- Options:
  - Shelters
  - Control Mast – Grounded Mount
  - Stairs, Full-length Handrails, Safety Signage

### PRODUCT CONFIGURATION OPTIONS:

---

- Integrate With Existing Building/Garage Door
- Portable Loading Dock – Mobile Design

**DOCKZILLA**