



# ADJUSTABLE HEIGHT LOADING DOCK **SPECS**

## **STRUCTURAL**

---

- Patented Impact-Resistance – absorbs trailer impact forces & remains in position
- High-strength steel frame
  - Bolt-down base plates
  - Premium laminated dock bumpers
  - Replaceable open bar traction grating
- Adjustable height front safety legs
  - Large adjustable height service range of 32"-56"
  - Patented no maintenance steel on steel legs

## **OVERALL LENGTH**

---

- 38ft. (8' Level Off Loading Deck + 30' Ramp) - Standard/Quick Ship
- Custom Level Off lengths & Longer Ramps available - Built to Order

## **CLEAR WIDTH (UNOBSTRUCTED, USABLE SPACE)**

---

- 96" - Standard
- 114" & 138" - Option
- Custom Clear Width available - Built to Order

## **CAPACITY (BASED ON FORKLIFT WEIGHT & MAXIMUM LOAD FOR 8 TRUCKS/DAY)**

---

- 16,000 lbs.
- 22,000 lbs
- 32,000 lbs.
- Custom Capacity available – Built to Order

## **DOCK LEVELER**

---

- Mechanical Edge of Dock Leveler (2" L x 72" W) service range +/-3" - Standard

## **SAFETY**

---

- Railing:
  - Pedestrian guardrails above 30" of elevation per IBC Code 1013.2
  - Handrails required at 48" of elevation per OSHA Code 1910.23 (c)(1 & 2)
- Ramp:
  - Features recessed sidecurbs for 180-degree forklift turning
  - 13" extra tall, unobstructed side curbs
- Vehicle Departure:
  - Wheel chocks to protect against trailer departure per OSHA 1910.178(k)
  - Trailer restraint per OSHA 1910.178(k) - Option
- Options: Ships Ladder, Full-length Handrails, Safety Signage
- Control Mast – Grounded Mount - Option

**DOCKZILLA**