



EXTRA WIDE LOADING DOCK **SPECS**

STRUCTURAL

- International design – fits in standard 40' shipping container
- High-strength steel frame
 - Replaceable open bar traction grating
 - Premium laminated dock bumpers
 - Steel-faced bumpers – Option
- Adjustable height front safety legs
 - Large adjustable height service range of 36"-56"
 - Patented no maintenance steel on steel legs
- Mobile design (custom fixed position available – Built to Order)
 - Exclusive solid 20" wheels
 - Patented Automatic Wheel Placement
 - Patented Automatic Kingpin Forklift Attachment

OVERALL LENGTH

- 40ft. (15' Level Off Loading Deck + 25' Ramp)
 - Ramp features recessed sidecurbs for 180-degree turning

CLEAR WIDTH (UNOBSTRUCTED, USABLE SPACE)

- 108" extra wide loading deck for forklift maneuverability
 - 85" wide narrower ramp allows forklifts to align/center larger loads

CAPACITY

- 16,000 lbs.
- 22,000 lbs.
- 32,000 lbs.

DOCK LEVELER

- Mechanical Edge of Dock Leveler (2' L x 72" W) service range +/-3" - Standard

SAFETY

- Handrails required at 48" of elevation per OSHA Code 1910.23 (c)(1 & 2)
- Wheel chocks to protect against trailer departure per OSHA 1910.178(k)
- Replaceable open bar traction grating
- Options: Stairs, Safety Signage, Control Mast – Grounded Mount

DOCKZILLA