



HIGH CAPACITY IMPLEMENT LOADING DOCK **SPECS**

STRUCTURAL

- Patented Impact-Resistance – absorbs trailer impact forces & remains in position
- High-strength steel frame
 - Bolt-down base plates
 - Premium laminated dock bumpers
 - Replaceable open bar traction grating
 - Replaceable wood deck - Option
- Adjustable height front safety legs
 - Large adjustable height service range of 32"-56"
 - Solar powered leg adjustment
 - Patented no maintenance steel on steel legs
 - High-capacity mobile loading dock – Option/Built to Order

OVERALL LENGTH

- 32ft. (No Level Off)
- 40ft. (No Level Off)
- Custom length ramps available - Built to Order

CLEAR WIDTH (UNOBSTRUCTED, USABLE SPACE)

- 120", 138", 168" - Standard
- Custom Clear Width available (such as 96", 108", 144", 192") - Built to Order

CAPACITY

- 60,000 lbs.
- 75,000 lbs.
- 85,000 lbs.

DOCK LEVELER

- Mechanical Edge of Dock Leveler (2' L x 72" W) – Standard
- Exclusive High Capacity 60,000 lb. Edge of Dock Leveler - Option

SAFETY

- Railing:
 - Pedestrian guardrails above 30" of elevation per IBC Code 1013.2
 - Handrails required at 48" of elevation per OSHA Code 1910.23 (c)(1 & 2)
- Ramp:
 - Recessed sidecurbs for 180-degree forklift turning
 - Tall, unobstructed side curbs
- Vehicle Departure:
 - Wheel chocks to protect against trailer departure per OSHA 1910.178(k)
 - Trailer restraint per OSHA 1910.178(k) - Option
- Options:
 - Control Mast – Grounded Mount
 - Ships Ladder, Full-length Handrails, Safety Signage

DOCKZILLA